
NOVARIX
LIGHTING

NRX-DLH013

RECESSED MOUNTED SPOT LIGHT





COB

FEATURES

Round recessed mounted mini spot light made of die-cast aluminium with white powder-coating
Body Color: Choice of black or semi white.

ceiling cutout of Ø75mm with a narrow mounting trim CCT 3cct(3000K-6500K) with an LED Output of 1200lm; high color rendering at an index of CRI90; after a lifetime of 50000h

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC33V-49V/300mA
Power	12W
Rated Input Current	0.200A
PF value	>0.95
Ingress Protection	IP54
Operating Temperature	-10—60℃
Dimmability (OPTIONAL)	Triac dimmable with **DIMMATE** driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra > 90
Colour temperature	2700K/3000K/4000K
Beam Angle	15°/24°/36°/60°

bridgelux LED RoHS 40°

40°

Model	Input	Color Temp	Lumen	Power	CRI	PF	Beam Angle
NRX-DLH013	220-240V	3000K/4000K/6600K	1200LM	12W	>90	>0.95	15°/24°/36°/60°

